

Australian Wool Testing Authority Ltd - trading as AWTA Product Testing A.B.N 43 006 014 106

1st Floor, 191 Racecourse Road, Flemington, Victoria 3031 P.O Box 240, North Melbourne, Victoria 3051 Phone (03) 9371 2400

## **TEST REPORT**

Client :	Big Panda F 5 Judds Cou Slacks Cree	irt			Test Number Issue Date Print Date	: :	20-00552 17/11/202 17/11/202	20
Sample I	Description	Clients Ref : "SPC" Rigid flooring planks Colour : Timber white End Use : Flooring Nominal Composition : Nominal Mass per Unit A Nominal Thickness :	Stone & Plastic	12.7kg/m2				
5 ISO 9239.1-2003		Reaction to Fire Tests fo Radiant Heat Source	or Floorings. Dete	ermination of	the Burning Be	havic	our using a	
		Date of Sample Arrival			28/10/2020			
		Date of Sample Arrival Date Tested			28/10/2020 16/11/2020			
				1		ł	Mean	
		Date Tested			16/11/2020	-	Mean ≥11	kW/m²

220787

47525

Smoke Value

Length

Width

Blistering

Australian Wool Testing Authority Ltd Copyright - All Rights Reserved



IAT/

Samples and their identifying descriptions have been provided by the client unless otherwise stated. AWTA Ltd makes no warranty, implied or otherwise, as to the source of the tested samples. The above test results relate only to the sample or samples tested. This document shall not be reproduced except in full and shall be rendered void if amended or altered. This document, the names AWTA Product Testing and AWTA Ltd may be used in advertising providing the content and format of the advertisement have been approved by the Managing Director of AWTA Ltd.

1

22

22

2

19

\_

12

Page 1 of 2

Mean

18

\_

Yes

%.min

%.min

3

13

\_





APPROVED SIGNATORY

(C)



Australian Wool Testing Authority Ltd - trading as AWTA Product Testing A.B.N 43 006 014 106

1st Floor, 191 Racecourse Road, Flemington, Victoria 3031 P.O Box 240, North Melbourne, Victoria 3051 Phone (03) 9371 2400

## **TEST REPORT**

Client :	Big Panda Flooring	Test Number	:	20-005527
	5 Judds Court	Issue Date	:	17/11/2020
	Slacks Creek QLD 4127	Print Date	:	17/11/2020

The test results relate to the behaviour of the test specimens of a product under the particular conditions of the test, they are not intended to be sole criterion for assessing the potential fire hazard of the product in use.

Sample was conditioned in accordance with BSEN 13238:2010 at a temperature of 23±2°C and relative humidity of 50±5% for a minimum of 48 hours prior to testing.

Results in accordance with section 8.4 have not been included in the report. They are available upon request.

Each specimen was clamped to a substrate of 6mm thick fibre reinforced cement board prior to testing.

HF30 not reported as flame out time occurred before 30 minutes.

220787

Australian Wool Testing Authority Ltd Copyright - All Rights Reserved

47525



the Managing Director of AWTA Ltd

Page 2 of 2



VICHAEL A. JACKSON B.Sc. (Hons)

relate only to the sample or samples tested. This document shall not be reproduced except in full and shall be rendered void if amended or altered. This document, the names AWTA Product Testing and AWTA Ltd

Samples and their identifying descriptions have been provided by the client unless otherwise stated. AWTA Ltd makes no warranty, implied or otherwise, as to the source of the tested samples. The above test results

may be used in advertising providing the content and format of the advertisement have been approved by



C